Oceanic Planks

TECHNICAL SPECIFICATIONS

Collection:	Oceanic
Country of Origin:	Australia
Colours:	15 Standard
Yarn:	100% Nylon
Surface Texture:	Patterned Cut Pile
Gauge:	39.4/10cm (1/10th Gauge)
Total Product Thickness:	7 (+/- 1.0)mm
Pile Height:	4.5 (+/- 1.0)mm
Pile Weight:	576.00g/m² (17oz)
Backing:	Enviro Bac®
Carpet Tiles & Planks Size:	250mm x 1000mm
Installation Method:	Direct Stick Recommended
Type:	Carpet Tiles and Planks
Units Per Box:	16.00
m² per box:	4

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	CRF 9.8kW/m² (Direct Stick)~
Colourfast to light:	(ISO 105-B-02-1994) 5-6
Light Reflectance:	Available on Request
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield® Antimicrobial Control
ACCS Rating:	Contract Extra Heavy Duty - 4 Star
Contract Guarantee:	15 Years Available on Request*
Smoke Value:	79% minutes (Direct Stick)
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4 Maximum Points - Certificate
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.

AVAILABILITY

Other Options:	Sculptured Loop Pile, Textured Loop Pile

Green Building Council Australia Member

Oceanic Planks



650
CORALEE



670
WHITSUNDAY



775
DORSAL



785
REFLECTION



790
EMPEROR



830
SEAFORTH



840
RIPTIDE



845
LONG ISLAND



850
ALTUM



860
KEPPEL



870
DUNK



875
PETRO



880
LIZARD



890
OXYGEN



940
ERSKINE

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.
Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear.
Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.
~Test results and certificates are available on request.
*Warranty is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the warranty please contact your GH Commercial Account Manager or our Head Office.